| | | 6 | 5 | | 1 | 3 | 3 | 2 | | | 1 | |
|---|--|--|---|-------------------|------|---|-----------------|--|---|----------------------|---------|-----|
| | | REVISIONS | | | | - | | | | | | 1 I |
| | REV. | REV. DESCRIPTION | | | BY | | | | | | | |
| | A | | | 11/15/2018 | RGM | | | | | | | |
| D | В | B UPDATE TO CURRENT REVISION | | 1/12/2021 | КС | | | | | | | D |
| | С | C ADD HOLES & SLOTS C/L ALIGNMENT TOLERANCE ± .008 | | 7/13/2021 | КС | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| с | | | | | | | | | (| .75 ^{+.031} | ┝──╼┤╞╾ | с |
| | | - | 28±.130 SLIDE TRAVEL |) | | (28±.07 | 79 SLIDE LENGTH | | | | | |
| | | | ° ° ° ° | 0 0 0 0 | | | | 0 0 00 | | | | |
| В | | (1.28)- | | | | | | | (| 2.99±.008 | | В |
| | INN | RECOMMENDED INNER SLIDE MEMBER: #10 MACHINE OR WOOD PAN HEAD SCREW FOR ALL THRU HOLES AND SLOTTED THRU HOLES. | | | | NUMBER: | | MATERIAL: | | | | _ |
| | OU | DUTER SLIDE MEMBER: | | | DESC | I-DS-3500-28L-5 | | | STEEL FINISH: | | | |
| | 1/4 HEX BOLT, #14 PAN HEAD WOOD SCREW FOR ALL THRU HOLES AND SLC | | |) SLOTTED THRU HO | LES. | 28" 3500 SERIES SLIDE, LEFT | | | ZINC PL | | LATE | |
| A | | DE SPACE = .750"783" TES: DIMENSIONS APPLY AFTI | er finish. | | | ISO 9001:2015 | RY | AD | NI | NC | • | |
| | 2. 3. 4. | BREAK ALL SHARP EDGES AND REMOVE ALL BURRS. MUST HAVE NO SCRATCHES, DINGS, DENTS OR SURFACE IMPERFECT | | | AN | | | PROPRIETARY NTAINED IN THIS DRAWING IS T S A WHOLE WITHOUT THE WRI | | | | A |
| | 5. 6. 7. 8. | ENSURE PACKAGING WIL | REMENTS. RE INDICATED BY: AQL SAMPLING PLAN UNLESS OTHERWIS L PROVIDE ADEQUATE PROTECTION DUP NOT DIMENSIONED ARE CONTROLLED BY | RING TRANSPORT. | | NSIONS ARE IN INCHES [mm] . XX [X] = ± 0.03 [0.8mm] (X [XX] = ± 0.015 [0.38mm] (] XXX] = ± 0.0080 [0.203mm] FRACTIONAL = ± 1/32" ANGULAR: ± 1.0" | | - SIZE NAME DATE | ENGR SALES KCHEN MB 3/6/2020 7/13/202 | QUALITY PN | REV C | |
| | | 6 | 5 | | 4 | | 3 | SCAL 2 | | NUT JUALE | 1 | - |

